

MSDS Sheet

Intumescent Latex

MATERIAL SAFETY DATA SHEET

WHMIS STATUS: NON CONTROLLED

SECTION 1: MATERIAL IDENTIFICATION

PRODUCT DESCRIPTION: INTUMESCENT LATEX WHITE

PRODUCT NAME: FIRE BARRIER INTUMESCENT PAINT

MANUFACTURER: CONTEGO INTERNATIONAL 1-800-434-6444 or 1-317-580-0665

HMIS CODE: HEALTH 0 FLAMMABILITY 0 REACTIVITY 0

PROTECTION: A

MATERIAL USE: ARCHITECTURAL FINISHES

SECTION 2: HAZARDOUS INGREDIENTS

INGREDIENT:

CAS #:

PERCENTAGE BY WEIGHT:

TLV: WHMIS CLASS: Not controlled.

LD50: (Rat, Oral):, LD50 (Rabbit, Dermal): LC50: not established

SECTION 3: PHYSICAL/CHEMICAL PROPERTIES

PHYSICAL PROPERTIES - liquid

SPECIFIC GRAVITY: 1.29

FREEZING POINT - 00 C

pH RANGE: 8.0-8.5

BOILING POINT - 100.0 C

SOLUBILITY IN WATER: soluble.

EVAPORATION RATE - same as water

VAPOR DENSITY - heavier than air

VAPOR PRESSURE: 17.5 MM HG (at 20 degrees C)

VOLATILE BY VOLUME = 56% APPEARANCE/ODOR: white, slight odor.

SECTION 4: FIRE & EXPLOSION HAZARD

FLAMMABILITY - not flammable

MEANS OF EXTINCTION - not applicable, not combustible.

FIRE/EXPLOSIVE HAZARD: Liquid paint will not burn but may spatter above boiling point.

FIRE FIGHTING EQUIPMENT: Self-contained breathing apparatus.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen and hydrocarbon.

SECTION 5: REACTIVITY DATA

STABILITY - stable under most conditions.

HAZARDOUS POLYMERIZATION - will not occur.

INCOMPATIBILITY - avoid strong oxidizing materials.

CONDITIONS TO AVOID - keep from freezing.

SECTION 6: TOXICOLOGICAL PROPERTIES

INHALATION - excessive exposure to vapors may cause headaches irritation of eyes, nose, throat and nausea.

EYE CONTACT - this material may be an eye irritant.

SKIN CONTACT - this material may be slightly irritating.

INGESTION - very low order of toxicity, no hazards are anticipated from ingestion incidental to handling.

CARCINOGENICITY: Not indicated.

MUTAGENICITY: Not indicated.

TERATOGENICITY: Not indicated.

REPRODUCTIVE TOXICITY: Not indicated.

SYNERGISTIC PRODUCTS: None known.

SECTION 7: PRECAUTIONS FOR SAFE USE & HANDLING

VENTILATION - Good general ventilation is sufficient in most cases.

SKIN PROTECTION - rubber, chemical resistant neoprene to prevent skin contact.

RESPIRATORY PROTECTION - yes, if ventilation is not adequate or when spraying.

EYE PROTECTION - goggles or face shield.

CLOTHING - clean if exposed to spill.

STORAGE AND HANDLING - keep from freezing. Store in a well ventilated area and away from source of heat (between 5-39 degrees C).

SPILL/LEAK PROCEDURES - avoid entry into sewers or waterways clean up with water before allowing to dry. Sodium chloride can be sprinkled on the spill, which may coagulate the latex and facilitate cleaning with water. Place waste in a closed container. Wear adequate protective equipment during clean up. Flush area with water.

SECTION 8: EMERGENCY FIRST AID PROCEDURES

INHALATION - remove source of contamination or remove victim to fresh air. If symptoms persist, obtain medical attention immediately. If breathing has stopped, use CPR and call for emergency medical attention.

EYE CONTACT - flush with large amounts of water for at least 15 minutes and seek medical attention if irritation persists.

SKIN CONTACT - wash with soap and water.

INGESTION - if swallowed induce vomiting. Immediately consult a physician.

SECTION 9: PREPARATION OF MSDS

DATE: 2/15/2000

PREPARED BY: RESEARCH AND DEVELOPMENT LABORATORY

SOURCES: THE INFORMATION USED TO PREPARE THIS MATERIAL SAFETY DATA SHEET IS BASED ON INFORMATION PROVIDED BY OUR RAW MATERIAL SUPPLIERS.

The information and recommendation on this Material Safety Data Sheet have been compiled from sources believed to be reliable and which represent the most current data in our possession on the subject at the date that this MSDS was prepared. No warranty or guarantee, expressed or implied, is made as to the accuracy or completeness of the data contained herein.

The user should consider the data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety of employees.